

SECTION 1 - PRODUCT IDENTIFICATION	
Product identifier/Trade name:	WAPOFLOC™/MD
Product code/Internal Identification:	None
Product use/Description:	Highly concentrated flocculant
Product chemical name:	Mixture
Chemical family:	N/Ap
MSDS preparation/review date:	June 27, 2013
Supplier identifier:	PINNACLE AQUATIC GROUP INC. Calgary (Alberta) Canada T2A 4T8 Téléphone: (403) 453-1944 or 1 855 453-1944
Manufacturer identifier:	Same as supplier.
Emergency phone number:	Canutec 613-996-6666. OR 1-800-463-5060.
WHMIS Classification:	E – Corrosive material



SECTION 2 - HAZARDS IDENTIFICATION	
Emergency Overview	
DANGER! Corrosive liquid. Causes respiratory and digestive tract, eye and skin irritation or burn.	
POTENTIAL HEALTH EFFECTS	
Primary entry route(s):	Skin contact, skin absorption, eye contact, ingestion and inhalation.
Effects of short-term (acute) exposure:	
Inhalation:	May cause irritation or burn to the nose, throat and respiratory tract. Symptoms may include burning sensation, sore throat, runny nose, coughing, wheezing, shortness of breath and difficulty breathing.
Skin:	Direct skin contact may cause moderate to severe irritation or burn.
Eye:	Direct eye contact may cause moderate eye irritation or burn. Symptoms may include redness, stinging, tearing and pain.
Ingestion:	May be harmful if swallowed. Ingestion may cause irritation or burn to the mouth, throat and stomach. Symptoms may include dizziness, drowsiness, nausea, headache and other central nervous system effects.
Effects of long-term (chronic) exposure:	
Refer to Section 11, Toxicological Information, for further information.	
Other important hazards:	
Refer to Section 11, Toxicological Information, for further information.	

SECTION 3 - CHEMICAL COMPOSITION / HAZARDOUS INGREDIENTS				
Hazardous Ingredients	CAS #	% (weight)	LD ₅₀ (route, species)	LC ₅₀ (species)
Aluminum chloride hydroxide sulphate	39290-78-3	15-40	N/Av	N/Av

SECTION 4 - FIRST AID MEASURES	
Inhalation:	Remove source of contamination or have victim move to fresh air. If not breathing, give artificial respiration. Obtain medical attention immediately.
Skin contact:	Wash contaminated area with running water for at least 15-20 minutes, while removing contaminated clothing. Obtain medical attention. Launder contaminated clothing before re-use.
Eye contact:	Immediately flush the contaminated eye(s) with gently flowing water for at least 15-20 minutes. Obtain medical attention.
Ingestion:	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. Obtain medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability: Does not burn under normal handling conditions.
Flash point (Method): N/Av
Lower flammable limit (% by volume): N/Av
Upper flammable limit (% by volume): N/Av
Sensitivity to mechanical impact: Not sensitive.
Sensitivity to static discharge: Not sensitive.
Auto-ignition temperature: N/Av
Suitable extinguishing media: Carbon dioxide, dry chemical powder and appropriate foam for surrounding products.
Special fire-fighting procedures/equipment:
 During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.
Hazardous combustion products: Carbon oxides and other irritating fumes and smoke.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:
 Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. Remove all ignition sources. Remove or isolate flammable and combustible materials. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).
Spill response/Cleanup:
 Ventilate area of release. Eliminate all sources of ignition. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.
Environmental precautions:
 Confine spill, preventing it from entering sewer lines or waterways. Dispose of as per local, state and federal regulations.

SECTION 7 - HANDLING AND STORAGE

Safe handling procedures:
 Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Do not use near welding operations, flames or hot surfaces. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Avoid breathing dusts, vapours or mists. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials such as strong oxidizing materials. Keep containers closed when not in use. Empty containers are always dangerous. Assume that empty containers contain residues which are hazardous.
Storage requirements:
 Store in a cool, dry, well-ventilated area out of direct sunlight, away from heat and ignition sources. Store away from incompatible materials. Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.
Incompatible materials:
 STRONG OXIDIZING MATERIALS, strong bases, some metals...

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure limits: There is no available data for the product. See below for individual ingredient exposure limits.

Ingredient	OSHA PEL		ACGIH TLV	
	TWA	STEL	TWA	STEL
Aluminum chloride hydroxide sulphate	N/Av	N/Av	N/Av	N/Av

Engineering controls:
 Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits.

Respiratory Protection:
 Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown.

Protective Clothing/Equipment:
 Chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact, must be worn during all handling operations. Wear protective chemical splash goggles to prevent mist, vapour and dust from entering the eyes. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

General Hygiene Considerations:
 Avoid generating high concentrations of dusts, vapours or mists. Avoid contact with skin and eyes. Avoid breathing dusts, vapours or mists. Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state, colour and odour: Clear to amber liquid with a slight odour.

Odour threshold: N/Av

pH : 2.1-3.1

Melting/freezing point: ~ -12°C

Coefficient of oil/water distribution: N/Av

Specific gravity or density (water = 1): 1.18-1.28

Evaporation rate (n-Butyl acetate = 1): N/Av

Boiling point: ~102°C

Vapour pressure: 17 mm Hg @ 20°C

Solubility in water: Soluble

Vapour density (Air = 1): N/Av

% volatile by volume: 90-95

SECTION 10 - REACTIVITY AND STABILITY DATA

Stability and reactivity: Stable under the recommended storage and handling conditions prescribed.

Polymerization: Hazardous polymerization will not occur.

Conditions to avoid: Incompatible materials (see Section 7).

Materials to avoid: Incompatible materials (see Section 7).

Hazardous decomposition products: Chlorine. Refer to 'Hazardous combustion products', Section 5.

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicological data:

There is no available data for the product itself, only for the ingredients. **For more details, refer to Section 3.**

Carcinogenicity: No ingredient is listed by IARC, ACGIH, NTP or OSHA as a carcinogen.

Teratogenicity, mutagenicity, other reproductive effects: N/Av

Skin sensitization: N/Av

Respiratory tract sensitization: N/Av

Conditions aggravated by exposure: N/Av

Synergistic materials: N/Av

SECTION 12 - ECOLOGICAL INFORMATION

Environmental effects: There is no available data on the product itself.

Important environmental characteristics: N/Av

Aquatic toxicity: N/Av

SECTION 13 - WASTE DISPOSAL

Handling and storage conditions for disposal: Store material for disposal as indicated in Handling and Storage (Section 7).

Methods of disposal: Review federal, provincial and local government requirements prior to disposal.

SECTION 14 - TRANSPORTATION INFORMATION

Transportation of Dangerous Goods Regulations (TDGR) :
 TDG Classification: UN3264; CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Aluminum chloride hydroxide sulphate); CLASS 8; PG III
 Special case: Product can also be shipped as a LIMITED QUANTITY according to TDG Section 1.17.

SECTION 15 - REGULATORY INFORMATION

WHMIS information:
 Product is regulated according to the Controlled Product Regulations (CPR) in Canada. Refer to Section 1 for the appropriate WHMIS classification. *This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.*

Canadian Environmental Protection Act (CEPA) information: The ingredients in this product are listed on the DSL.

United States OSHA information:
 This product is regulated according to OSHA. This MSDS contains all the information required by OSHA.

United States TSCA information: The ingredients in this product are listed on the TSCA.

National Fire Protection Association (NFPA):
 HEALTH: 2 FLAMMABILITY: 0 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 1 & 3.
 HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

New Jersey Labeling Requirements: Ingredients to be disclosed on product labelling: Refer to Section 3.

California Proposition 65: This product does not contain chemicals that are known to the State of California to cause cancer or other reproductive harm.

SECTION 16 - OTHER INFORMATION

Prepared by: NSS ENTREPRISE INC.
Telephone number: Tel. 514-239-8785 or (450) 438-4416 or 1-800-433-0590

References:

1. Material Safety Data Sheets from manufacturer/supplier.
2. CSST, Répertoire Toxicologique, Les produits, 2013.
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2013.

Abbreviations:

ACGIH	American Conference of Governmental Industrial Hygienists
AIHA	American Industrial Hygiene Association
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
LC	Lethal concentration
LD	Lethal Dosage
N/Ap	Not applicable
N/Av	Not available
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. End of the MSDS